

Follow the instructions below:

1. Add the following record to the *services.config* files located at *..\Terasoft.WebApp\ServiceModel\http* and *..\Terasoft.WebApp\ServiceModel\https* catalogs:

```
<service name="Terasoft.Configuration. AletPDFReportImageService. AletPDFReportImageService">  
  <endpoint name=" AletPDFReportImageServiceEndPoint"  
    address=""  
    binding="webHttpBinding"  
    behaviorConfiguration="RestServiceBehavior"  
    bindingNamespace="http://Terasoft.WebApp.ServiceModel"  
    contract="Terasoft.Configuration. AletPDFReportImageService. AletPDFReportImageService " />  
</service>
```

2. Perform the following changes in the *..\Terasoft.WebApp\Web.config* file:
Add the `<location>` element defining the relative path and access rights to the service

```
<location path="ServiceModel/AletPDFReportImageService.svc">  
  <system.web>  
    <authorization>  
      <allow users="*" />  
    </authorization>  
  </system.web>  
</location>
```

In the `<appSettings>` element change the value for the "AllowedLocations" key by adding the relative path to the service into it:

```
<add key="AllowedLocations" value="[Previous values];ServiceModel/AletPDFReportImageService.svc" />
```

3. Put the file *AletPDFReportImageService.svc* in the *..\Terasoft.WebApp\ServiceModel*.
4. Reload the application pool in IIS.