

**Follow the steps:**

1. In file .\Terasoft.WebApp\ServiceModel\http\services.config **add section:**

```
<service name="Terasoft.Configuration.AletTrelloConfigurationService.AletTrelloConfigurationService">
  <endpoint name="UsrCustomConfigurationServiceEndPoint"
    address=""
    binding="webHttpBinding"
    behaviorConfiguration="RestServiceBehavior"
    bindingNamespace="http://Terasoft.WebApp.ServiceModel"
    contract="Terasoft.Configuration.AletTrelloConfigurationService.AletTrelloConfigurationService" />
</service>
```

2. In file .\Terasoft.WebApp\ServiceModel\https\services.config **add section:**

```
<service name="Terasoft.Configuration.AletTrelloConfigurationService.AletTrelloConfigurationService">
  <endpoint name="UsrCustomConfigurationServiceEndPoint"
    address=""
    binding="webHttpBinding"
    behaviorConfiguration="RestServiceBehavior"
    bindingNamespace="http://Terasoft.WebApp.ServiceModel"
    contract="Terasoft.Configuration.AletTrelloConfigurationService.AletTrelloConfigurationService" />
</service>
```

3. In file. \Terasoft.WebApp\Web.config

**add section, relative path and access rights to the service:**

```
<location path="ServiceModel/AletTrelloConfigurationService.svc">
  <system.web>
    <authorization>
      <allow users="*" />
    </authorization>
  </system.web>
</location>
```

In <appSettings> change value for "AllowedLocations", add path to service

"ServiceModel/ AletTrelloConfigurationService.svc"

Example: <add key="AllowedLocations" value="...;ServiceModel/AletTrelloConfigurationService.svc" />

4. In directory ..\Terasoft.WebApp\ServiceModel **put the file AletTrelloConfigurationService.svc**

5. **Restart IIS pool.**